

Reflector

U-LI Goodlite's range of reflectors is specially designed for directional light control. It can be easily added on to bare batten for symmetrical or asymmetrical light distribution. It is available in epoxy powder coated and oven baked or high reflectance aluminium mirror.

Focusing light to areas required.

Shield bright illumination from normal view angles.

Easy attachment to standard batten fittings.

Dimension of Fittings

| Model | Wattage (Tubes) | Length | Profile |
|-----------|-----------------|---------|---------|
| GMR 120 | 1 x 18W | 610 mm | |
| GMR 140 | 1 x 36W | 1220 mm | |
| GMR 158 | 1 x 58W | 1520 mm | |
| GMR 170 | 1 x 70W | 1820 mm | |
| GMR 220 | 2 x 18W | 610 mm | |
| GMR 240 | 2 x 36W | 1220 mm | |
| GMR 258 | 2 x 58W | 1520 mm | |
| GMR 270 | 2 x 70W | 1820 mm | |
| GMR 120/H | 1 x 18W | 610 mm | |
| GMR 140/H | 1 x 36W | 1220 mm | |
| GMR 158/H | 1 x 58W | 1520 mm | |
| GMR 170/H | 1 x 70W | 1820 mm | |
| GMR 220/H | 2 x 18W | 610 mm | |
| GMR 240/H | 2 x 36W | 1220 mm | |
| GMR 258/H | 2 x 58W | 1520 mm | |
| GMR 270/H | 2 x 70W | 1820 mm | |

For Ordering

/AR : Add /AR for Aluminium Mirror Reflector



Accessories / Options



GLC 91



GLC SL



GLC CLK



GLC DC



AR Reflector